

# THANK YOU FOR CHOOSING A MORLEY PEDAL. YOU NOW OWN THE BEST PEDAL MADE!

Please take a few minutes to familiarize yourself with the features of your new pedal. We hope you enjoy using it as much as we enjoyed building it.

## ABOUT OUR M2 SLIDE POT:

The M2ME Mini Voltage Control Pedal is designed to use a slide pot to control parameters of the device it's hooked up to. A durable Monofilament cable is used to move the internal slide pot when the foot treadle is moved. We have developed a special lubricant to extend the slide pot life and prevent static and scratchiness of typical rotary pots.

## ABOUT THE CONNECTIONS:

**NORMAL:** Plug from device controller / pedal jack using 1/4" Stereo cable. Stereo cables are also known as TRS (Tip/Ring/Sleeve) cables.

**ALTERNATE:** Plug from device controller / pedal jack using 1/4" Stereo cable. Stereo cables are also known as TRS (Tip/Ring/Sleeve) cables. If your M2 Mini Expression works in reverse when using the NORMAL jack, use the ALTERNATE jack to correct.

## USING AN AC ADAPTER:

The M2ME is a passive device (no power is required)

## USING A BATTERY:

The M2ME is a passive device (no power is required).

## ONE YEAR WARRANTY

All Morley® pedals are warranted for one year from date of purchase with a copy of dated purchase receipt. To obtain warranty service, contact dealer where pedal was purchased.

## M2 MINI EXPRESSION (MODEL M2ME) FEATURES:

- **Slide Pot:** Internal slide pot and durable monofilament control Expression function.

## M2ME SPECIFICATIONS:

Power: None Required

Dimensions: 6.75" L x 4.5" W x 2.75" H

Current Draw: N/A

Slide Pot: 10K Linear Taper

Weight: 2.1 lb./ 0.95 kg

[www.morleyproducts.com](http://www.morleyproducts.com)

